

### Beinlich Gearpump 2-225 ( circa 200 running hours)

€ 200,00	per stuk (excl btw en transport)
€ -	totaal: (excl btw en transport)

code 1724-18/1	ZL
Direction of rotation	CW or CCW
P suction minimum	-0,4 bar
P suction maximum	+ 1,0 bar
P press side	180 bar
Temp range	-10 C upto 80 C
Visc range	16-1000 mm2/s
Speed range	200-3600 rpm
Capacity at 1450 rpm	1,5 m3/h
Power demand	0,25kW-1,12 kW(at2-25 bar)
Suction/Discharge flange	SAE Flange 3/4 "3000 PSI
Shaft end	18h6 DIN 6885
Safety valve	40 bar

### 2x Beinlich Gearpump 4-465 met elektromotor

€ -	per stuk (excl btw en transport)
€ 6.300,00	totaal: (excl btw en transport)

code 1724-18/2	ZL
Direction of rotation	CW and CCW
P suction minimum	-0,4 bar
P suction maximum	+ 1,0 bar
P press side	180 bar
Temp range	-10 C upto 80 C
Visc range	16-1000 mm2/s
Speed range	200-3600 rpm
Capacity at 1450 rpm	33 m3/h
Power demand	4 kW-15 kW(at2-25 bar)
Suction/Discharge flange	SAE Flange 3 1/2 "3000 PSI
Shaft end	32h6 DIN 6885

### 5x Beinlich Gearpump 4-465

€ 1.500,00	per stuk (excl btw en transport)
€ 7.500,00	totaal: (excl btw en transport)

code 1724-18/3	ZL
Direction of rotation	CW and CCW
P suction minimum	-0,4 bar
P suction maximum	+ 1,0 bar
P press side	180 bar
Temp range	-10 C upto 80 C
Visc range	16-1000 mm2/s
Speed range	200-3600 rpm
Capacity at 1450 rpm	33 m3/h
Power demand	4 kW-15 kW(at2-25 bar)
Suction/Discharge flange	SAE Flange 3 1/2 "3000 PSI
Shaft end	32h6 DIN 6885



## 2x Beinlich Gearpump 5-700

€ 2.000,00 per stuk (excl btw en transport)

€ 4.000,00 totaal: (excl btw en transport)

code 1724-18/4 ZL

Direction of rotation CW and CCW  
P suction minimum -0,4 bar  
P suction maximum + 1,0 bar  
P press side 180 bar  
Temp range -10 C upto 80 C  
Visc range 16-1000 mm<sup>2</sup>/s  
Speed range 200-3600 rpm  
Capacity at 1450 rpm 61 m<sup>3</sup>/h  
Power demand 10 kW-35 kW(at 2 - 16 bar)  
Suction/Discharge flange SAE Flange 3/4 "3000 PSI  
Shaft end 32h6 DIN 6885



## Kracht Gearpump KF 6/400

€ - per stuk (excl btw en transport)

€ 1.500,00 totaal: (excl btw en transport)

code 1724-18/5 ZL

Direction of rotation CW or CCW  
P suction minimum -0,4 bar  
P suction maximum + 1,0 bar  
P press side 25 bar  
Temp range -10 C upto 150 C  
Visc range 12-15000 mm<sup>2</sup>/s  
Speed range 200-2000 rpm  
Capacity at 1450 rpm 34,5 m<sup>3</sup>/h  
Power demand 5,8kW-28,3 kW(at2-25 bar)  
Suction/Discharge flange SAE Flange 4"  
Shaft end 38k6 DIN 6885



## 4x leistriz pump incl elektromotor

€ 1.000,00 per stuk (excl btw en transport)

€ 4.000,00 totaal: (excl btw en transport)

code 1724-18/6 ZL

Type L3MF 25/35 IFOKS-G LRS testpress 120 bar  
capacity: 0,4 m<sup>2</sup>/h/100 bar

Elektromotor: AEG 1,8 kW/60Hz/ 1145 rpm

